

BRAKES

I> CHASSIS No. 219001

Data

Front S56 P.S.V., S66

make Lockheed
type 2 piston pin slider caliper
brake disc 300mm dia. ventilated
pistons 2 off x 50mm dia.
pad material Don 7250 or Ferodo 3422
(min. pad thickness 4mm)

REAR S46, S56 Haulage

make Girling
type duo-servo drum - auto. adjust
size 308 x 102 (12.125" x 4")
wheel cylinder 1 x 20,64 (^{t3}/16") dia.
lining material **Ferodo** primary - 2601 F (thin)
secondary - 2636F (thick)
lining length primary 296mm secondary 338mm

REAR S56 P.S.V.

make Lockheed
type duo-servo drum - auto. adjust
size 330 x 140 (13" x 5.5")
wheel cylinder 20,6 (0.81 ") dia
lining material Ferodo primary- (thin) AM 1
secondary - (thick) AM 14
lining length primary 316 secondary 360

REAR S66

make Girling
type duo-servo drum - auto. adjust
size 308 x 102 (12.125" x 4")
wheel cylinder 1 x 22,22 (%") dia.
lining material Ferodo primary - 2601 F (thin)
secondary - 2636F (thick)

lining length primary 296mm secondary 338mm

PARKING BRAKE

type handlever and cable

overall ratio19.44:1