Index

SECTION M

BRAKES

	SECTION
INDEX DESCRIPTION (INC. DIAGRAMATIC LAYOUT) DATA TIGHTENING TORQUES SPECIAL TOOLS FAULT DIAGNOSIS (VAC./HYD.) FAULT DIAGNOSIS (AIR/HYD.)	. MAO10 . MAO20 . MAO30 . MAO40 . MAO50
FRONT BRAKES 4 x 46M Disc Brake Caliper	. MA120 . MA130
REAR BRAKES 12½ x 4 DUO SERVO	MA150 MA160
BLEEDING THE HYDRAULIC SYSTEM	MA190
MASTER CYLINDER (VAC./HYD.) MASTER CYLINDER (AIR/HYD.) HAULAGE MASTER CYLINDER (AIR/HYD.) P.S.V.	IVIAZ IV
SERVO UNIT (VAC./HYD.) TANDEM ACTUATOR (AIR/HYD.) HAULAGE TANDEM ACTUATOR (AIR/HYD.) P.S.V	1417200

Index

SECTION
HANDBRAKE AND LINKAGEMA300
SPRING BRAKE AND COMPENSATOR
VALVES Dual Brake Vaive
ANTI-FREEZE UNIT
AIR LINE FILTER MA455
LOW PRESSURE WARNING SWITCHES MA460
AIR RESERVOIRS AND FITTINGS MA500
COMPRESSOR MA600

Index



WARNING CONTAINS ASBESTOS

Breathing asbestos dust is dangerous to health.

Follow safety instructions.

ASBESTOS ALERT

The vehicle described in this publication incorporates components containing asbestos.

Working with them can create dust. Breathing this dust is harmful. Cases of asbestos related cancer have been reported in garage workers.

The dangerous jobs are: • cleaning brake assemblies • cleaning clutch housings • grinding brake linings • drilling brake linings • sweeping floors

Brake and clutch linings and disc pads may contain asbestos. If in doubt assume that they do.

WHO IS AT RISK?

Anyone in the garage could be at risk. There is no known safe level of asbestos dust. But the more dust you breathe the greater the chance of lung damage.

The problem is that the dust particles are too small to be seen by the naked eye. And the diseases caused can take years to develop.

Don't put the brakes on your life. Avoid breathing asbestos dust. Prevent dust getting into the air. Follow the GARAGE WORKERS' ASBESTOS CODE.

GARAGE WORKERS' ASBESTOS CODE

- 1. DON'T blow dust out of brake drums or clutch housings with an air line.
- 2. DO use properly designed drum cleaning equipment which prevents dust escaping, or use clean wet rags to clean out drums or housings. Put used rags in a plastic waste bag while still wet.
- 3. DON'T grind or drill linings unless the machine has exhaust ventialtion or there is a ventilated booth to do the work in.
- 4. DON'T use brushes to sweep up dust.
- 5. DO use a special (Type H) vacuum cleaner to remove dust.
- 6. DO wet dust thoroughly and scrape it up if you haven't got a vacuum.
- 7. DO wear the protective clothing, such as overalls, provided by your employer.
- 8. DON'T take the protective clothing home. It should be cleaned by your employer.
- 9. DON'T use equipment if it is not maintained and checked. Ask to see the examination reports for ventilation systems.